



PUSH OUT TRAILER

ALUMINUM PUSH OUT TRAILER

DYNA-HAULER

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*

Push out trailers eliminate the possibility of rollovers common with dump trailers during the unloading cycle.

Ideal for sludge and material hauling.

Our aluminum push out trailers eject horizontally and are uniquely designed to safely haul and discharge sludge and other like materials. Because of their size and stability, our trailers allow owners and operators to haul maximum payload with less chance of rollover.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trailers you want - we'll build them to your specification and application.

J&J TRUCK BODIES & TRAILERS
Built for the Long Haul®

Call today! 800.777.2671
www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR ALUMINUM PUSH OUT TRAILERS



Trailer shown with optional bulkhead ladder (Man door standard). Ejector controls mounted on driver's side bulkhead.



Ejector ram cylinder sized to completely unload trailer. Replaceable UHMW wipers on sides and bottom.

ALUMINUM STANDARD SPECIFICATIONS*

Length: 38'6"
Height: 66"
Side Panels: 3/16" 5454-H34
Floor: 3/8" 5454-H34
Top Rail: 9" extruded boxed channel 6061-T6
Bottom Rail: 4" extruded bottom rail 6061-T6
Side Posts: Extruded vertical posts 5/32" x 3¾" wide 6061-T6
Understructure: 4"x4" extruded boxed channel crossmembers on 16" centers. Dual frame running full length of trailer consisting of (2) 7 "T" section long members interlocked with crossmembers. Welded directly to trailer floor. Crossmember on 16" centers.
Fifth Wheel Assembly: 3/8" steel plate, 2" SAE King Pin.
Ejector: 1/4" face plate backed by rigid brace members to withstand discharge thrust. UHMW Guide shoes top, bottom, and sides. Replaceable UHMW wipers on sides and bottom.
Ejector Hydraulic System: Ejector ram cylinder sized to completely unload the trailer. 8" diameter, 5 stage standard 3-line system, tank on tractor, dump valve on trailer for fast retraction.

Tailgate: Top hinged, side swing or hydraulic operated tailgate. Full seals standard for sludge applications (Side swing or hydraulic tailgates optional).
Suspension: REYCO 21B 52,000# single leaf system with cast hangers.
Hubs: Steel hub piloted.
Wheels: 24.5" x 8.25" steel hub piloted.
Tires: 11R24.5 14 ply.
Axles: Dana D-22 25,000# with 16½" x 7" brakes.
Lighting: Truck-Lite® shock proof, harness system.
Landing Gear: Holland Mark V 2-speed with sand shoes. 50,000# lift, 180,000# static load capacity.
Other Standard Features: Mud guards, mud flaps, ladders, and tarp rails.



Trailer shown with optional hydraulic tailgate and full rubber seal.

*Standard specifications may vary according to customer's preferences and requirements. Many options available.

Call your J&J sales representative today!



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

ISO 9001:2015 Certified
"Our Commitment to Quality"



**10558 Somerset Pike
 Somerset, PA 15501 USA
 Phone: 814.444.3400
 Fax: 814.443.2621
 Toll Free: 800.777.2671 (USA only)
 Email: sales@jbbodies.com
 www.jbbodies.com**