



Optional polished aluminum provides a great look.

The DynaHauler/MH EVO Dump Body features smooth and aerodynamic sides.

J&J's EVO series material haulers are an ideal solution if you're hauling aggregates like asphalt, sand, stone, gravel, or coal. The reinforced interlocking double wall panels provide excellent insulation for materials like asphalt. The interior wall is designed to absorb impact, while the outside of the dump body remains in good condition. You can rely on the rugged DynaHauler®/MH EVO for your material hauling needs.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trucks you want - we'll build them to your specification and application.



Call today! 800.777.2671
www.jjbodies.com

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*

EVO

DYNAHAULER

SPECIFICATIONS & DIMENSIONAL DATA FOR DYNAHAULER/MH MATERIAL HAULER EVO DUMP BODIES



The reinforced double wall side panels create excellent insulating properties for asphalt haulers.



The interior wall makes outside pings and dents a thing of the past, increasing the re-sale value of these dump bodies.

ALUMINUM STANDARD SPECIFICATIONS*

Lengths: 13' to 20'.

Side Panels & Bulkhead: 9½" wide, double wall, 6005-T5 alloy side panel with two vertical stiffening ribs; .250 connected joint thickness, .135 inner wall, .100 outer wall, 40,000 PSI yield, 95 Brinell hardness.

Floor: ¼" - 5454 - H34.

Understructure: 4" boxed crossmembers on 12" centers, 2.70# per ft. 6" I-beam longitudinals, 5.10#per ft. 2" extruded rubber mounting strip.

Cab Protector: 3/16" ½ length dual offset.

Tailgate: 60" high, 3 panel, 1/4" with offset top hardware.

Hydraulic System: Front mount telescopic cylinder, PTO & pump, 3-line safety system, variety of controls and instrumentation to suit requirements.

Lighting: Meets FMVSS 108 guidelines, LED standard, variety of configurations and warning modules available.

Popular Options: Polished aluminum • Spreader apron • Air operated pump and premium Chelsea PTO • Hot shift • Body heat • Tarp system • Tool boxes • Coal doors • Oak sideboards

For a complete list of options, call J&J today!



Polished aluminum is one of the most popular options on J&J EVO bodies.

		BODY LENGTH							
SIDE		13	14	15	16	17	18	19	20
VOLUME (cu. yds)	54	15/18	17/19	18/21	19/22	20/23	22/25	23/26	24/28
	60	17/20	19/21	20/23	21/24	23/26	24/27	25/29	27/30
	66	19/21	20/23	22/25	24/26	25/28	27/30	28/31	30/33
	72	21/22	21/25	24/27	27/28	27/30	30/33	31/33	33/36

*Standard specifications may vary according to customer's preferences and requirements. Many options available.

Call your J&J sales representative today!



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

ISO 9001:2015 Certified

"Our Commitment to Quality"



**10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 814.444.3400
Fax: 814.443.2621
Toll Free: 800.777.2671 (USA only)
Email: sales@jjbodies.com
www.jjbodies.com**



Distributed by: