



Optional polished aluminum and additional lighting is available as shown in photo.

Aluminum body, steel frame dump trailers are engineered for excavation and construction material hauling.

FTA aluminum body, steel frame dump trailers are built to handle a variety of demanding applications. Whether you're involved in excavating, construction material hauling, or any similar application, we can build you a dump trailer that's loaded with standard features and comes with a wide variety of popular options.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the trailers you want - we'll build them to your specification and application.



Call today! 800.777.2671
www.jjbodies.com

FRAME TRAILER
ALUMINUM

DYNAMA HAULER

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*

SPECIFICATIONS & DIMENSIONAL DATA FOR FRAME TRAILER ALUMINUM EVO SERIES



STEEL STANDARD SPECIFICATIONS*

Length: 22' - 35'.
Side Panels: 54", 60", 66" or 72" high, 5/32" 5454-H34 with 6" top boards.
Floor: 1/4" 5454-H34 solid welded with radius corners.
Top & Bottom Rail (30'+): 9" x 4" 6061-T6 top rail. 9" x 4" extruded bottom rail 6061-T6.
Side & Rear Posts: Extruded side posts (6061-T6) on 30" centers. Rear posts are 4" x 3" x 3/8" vertical angle, interlocked with rub rail and 4" x 2" x 3/16" horizontal tubing below floor, reinforced with formed 12" x 4" section.
Understructure: 4" boxed crossmembers on 15" centers, 6061-T6. Longitudinals are 6" x 6" x 1/2" angles (6061-T6) running full length, welded to all crossmembers and gusseted to every fourth crossmember.
Tailgate: 60" high, 3/16" 5454-H34, 3 panel.
Lighting: Truck-Lite® sealed and shock proof system.
Axles: Dana D22 25,000 lb., 5" round.
Brakes: 161/2" x 7" or 3/4" air operated with ABS.
Frame: 16" deep wide flange beam (31 lb./ft.). High-tensile steel.
Hoist: Custom front mount telescopic.
Suspension: REYCO 21B 52,000 lb., 4-spring.

King Pin: Holland 3/8" A-36 steel.
Landing Gear: Holland Mark V 2-speed, with sand pads. 180,000 lb. static load capacity.
Tires: 11R24.5, 14 ply.
Wheels: 24.5" x 8.25" steel.
Other standard features: Oil seals • Mud guards & mud flaps • Steps • Shovel hangers • Tarp bars • Paint

POPULAR OPTIONS

Side Panels: A variety of heights and thicknesses are available. Side posts on 24" centers. Horizontal side braces.
Floors: 3/8" thick 5454-H34 at rear 1/3 of body.
Understructure: Crossmembers on 12" centers.
Tailgates: High-lift or swing gate with rubber seal. Sloped or vertical.
Tarping: Tarps, tarp bows and tarp baskets. Manual, electric or hydraulic; slide, arm or roll tarpers.
Other: Tire carrier • Lift axles • Catwalk/Ladders • Tool box • Spreader apron • Coal door • Wet-lines • Fifth wheels • On-board scales • Fenders • Vibrators • Centrifuse drums • Aluminum hubs • Square axles • Aluminum frame • Shock mounted pad between frame and under-structure • Special overhangs • 6" I-beam longitudinals

DUMP TRAILER DATA

Lengths	22' to 35'
Side Height	54' to 72'
Overall Height	Variable, consult your J&J Representative*
Gate Height	54' to 72'
Tire to end of floor	4"
King pin to front of trailer	18" Standard
King pin to center of suspension	Variable, consult your J&J Representative*
Center of hinge pin to end of floor	6"
*13'6" maximum available. Dimensions may vary slightly and are subject to change without notice.	


*Standard specifications may vary according to customer's preferences and requirements.
 Many options available. **Call your J&J sales representative today!**



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

ISO 9001:2015 Certified
 "Our Commitment to Quality"



J&J TRUCK BODIES & TRAILERS®
 Built for the Long Haul®

10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 814.444.3400
Fax: 814.443.2621
Toll Free: 800.777.2671 (USA only)
Email: sales@jbjbodies.com
www.jbjbodies.com

Rev: 0916-1