

The perfect solution for the serious scrap hauler.

If you are a scrap hauler, you'll appreciate the reduced weight, increased wear life, and the superior strength of our DynaHauler/SST steel scrap dump trailer. We've constructed this trailer with high hard steel and replaced the crossmembers with high hard cushioned floor plates. By doing this, we've not only reduced the weight of the trailer, but the cushioned floor plates also serve to absorb impact while maintaining the integrity of the trailer.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trailers you want - we'll build them to your specification and application.



The Right Steel for Your Body.™

DYNNHAULER*

TRAILER

ISO 9001:2015 Certified. Quality products, quality workmanship.

J&J Truck Bodies & Trailers is a division of Somerset Welding & Steel, Inc.



Call today! 800.777.2671 www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR Steel Scrap Dump Trailer



The body design is a constant taper from front to rear, which allows the material to slide out easier, eliminating load hang-ups while discharging the payload.



J&J dump trailers set the standard for quality and reliability.

STEEL STANDARD SPECIFICATIONS*

Body: Steel

Lengths: 22' to 40'

Width: 96" or 102" outside

Height: 54" to 66" with or without inverted

End of floor to end of frame: 4" max Tire to end of body: 12" maximum

Material:

Sides: 1/8" to 1/4" high hard steel Floor: 1/8" to 1/4" high hard steel Front: 1/8" to 3/16" high hard steel

Fenders: 12 ga. high tensile formed steel, over

suspension only, full length optional Top Rail: 4" wide x 6"x structural steel tube Side posts: 3/16" high tensile formed steel (3 total), (1) rear, (1) center, and (1) front -

Note: Front post will be covered by the formed front

Understructure:

Crossmembers: cushioned floor plates (1/4" steel plate)

Longitudinals: 4" x 4" x square tubing, run-

ning full length

Tailgate:

Style: Standard barn door only (top hinge also avail.)

Height: 54" to 66"

Number of panels: 3 Sheet: 1/8" to 1/4" high hard steel

Controls: Manual over center positive latching system roadside.

Paint: Frame: One color SherwinWilliams

Genesis Lead Free

Body: One color SherwinWilliams Genesis

Lead Free

Accessories:

Ladders: (1) bulkhead

Shovel Bracket: Bulkhead on driver's side

Chassis: Steel Lengths: 22' to 40'

Beam: 16" @ 31 lb./ft HiTen steel

King Pin Setting: 18"

Upper Coupler Plate: 3/8" A36 with 2 7/8"

ASME pin

Landing gear: Holland MK-V 180,000 lb.

2-speed

Bumper: ICCType

Cylinder: Size determined by length of trailer

Primary Suspension: Hutch Single Point, 60.000 lb.

Gear:

Primary Axles: Dana Spicer D22 25,000 lb. cap with Haldex automatic slack adjusters

Aux. Suspension: Optional

Aux Axle Control: Specify Brakes: 16 1/4" X 7" X 1/4" air operated with 4S2MABS-Wire ABS through center

pole of 7 way receptacle. Hubs & Drums: Outboard Mounted 10-hole

steel hub piloted (Unimount)

Wheels: 8.25" X 24.5" Steel Hub Piloted Tires: B.F.Goodrich ST-220, 11R24.5" 14 ply

Electrical: 12 volt TruckLite®, in rear frame, and side marker lights.

7-pole receptacle on front frame. Mud flaps: (3) full across



Lighter weight high hard steel cushioned floor plates absorb impact while maintaining the integrity of the trailer.



The Right Steel for Your Body.™

*Standard specifications may vary according to customer's preferences and requirements. Many options available

Call your J&J sales representative today! ISO 9001:2015 Certified





'Our Commitment to Quality



10558 Somerset Pike Somerset, PA 15501 USA Phone: 814.444.3400 Fax: 814.443.2621

Toll Free: 800.777.2671 (USA only)

Email: sales@jjbodies.com

www.jjbodies.com Rev: 0916-1